



Effort-free cleaning

Available in the version with 1 disc brush of 51 and 55 cm.



L20/22 B-E is suitable for the maintenance cleaning of commercial surfaces up to 1400 sq.m.: guaranteed cleanliness without training



L20/22 B-E is a walk-behind scrubbing machine available in electric or battery versions, with 1 disc brush of 51 cm (L20) or 55 cm (L22) working width.



L20/22 B can work for up to 1 hour over a surface of 2000 sq.m. with a single tank of detergent solution.
Up to 2 hours autonomy with a single energy charge.



The amount of solution can be regulated according to the real cleaning needs.

PLUS

Compared to a traditional scrubbing machine, L20/22 offers the following benefits:

- It can be used even by untrained operators
- High productivity and reduced consumption levels
- Squeegee made of reinforced, corrosion resistant plastic material
- Easy maintenance at the end of the work
- Easy to move from one place to another



L20 E



Access to the battery compartment is quick and easy.
On request, the L20/22 B models can be fitted with the following batteries:
- 12 V/102 Ah (2)
- Gel 12V/75 Ah (2)



L20 B

L20/ 22 is easy to use,
transport and sanitise



L20/22 B-E is fitted with a new squeegee in a reinforced (Patent Pending) plastic material that is corrosion resistant. The automatic uncoupling system protects the squeegee when accidentally impacted.



With L20/ 22 B-E, you're ready to work at once!

Just:

1. Fill with the detergent solution - 2. Lower the squeegee - 3. Switch on the machine and the vacuum function - 4. Start working



Maintenance is easy and effort-free.

That means machine efficiency is guaranteed over time!



The special design of the tank ensures full emptying for the final rinse



Solution tank emptying



To obtain excellent cleaning and drying results, it is important to keep the filter clean, along with the suction hose connected to the squeegee



On request, the L20/ 22 B can be fitted with on board battery charger, so that recharging operations are quick and simple to perform

L22 B-E perfect cleaning along walls



Automatic brush coupling and uncoupling



L22 B-E equipped with solenoid valve
The solenoid valve automatically stops the flow of water when the machine is not working or is stopped by the operator.
(optional for L20 B-E)

STANDARD EQUIPMENT L20 B-E

With PPL 0,6 brush of 51 cm

Squeegee of 68 cm

STANDARD EQUIPMENT L22 B-E

With PPL 0,6 brush of 55 cm

Squeegee of 78 cm

Solenoid valve kit and filter

TECHNICAL DESCRIPTION		L20 B	L20 E	L22 B	L22 E
Squeegee width	mm	680	680	780	780
Disc brushes Ø	(n.) mm	(1) 510	(1) 510	(1) 550	(1) 550
Brush motor	V/W	24/560	220-230/ 750	24/560	220-230/ 750
Brush rpm	rpm	135	135	135	135
Brush pressure	kg	27,5	27,5	27,5	27,5
Suction motor	V/W	24/310	230/450	24/310	230/450
Type of drive	-	semi aut.	semi aut.	semi aut.	semi aut.
Battery compartment dimensions (L x h x w) mm		330 x 270 x 345	-	330 x 270 x 345	-
Max gradient at full load	%	2	2	2	2
Batteries	V/ Ah C20	12 V/ 102 (2)	-	12 V/ 102 (2)	-
Batteries weight	kg	54	-	54	-
Machine weight (without battery)	kg	62	62	62	62

	Working width mm	Brush pressure	Power supply V/ traction Voltage V/ Frequency Hz/ traction	Solution tank l	Recovery tank l	Working capacity up to m ² /h	Machine dimensions mm L x H x W	Machine weight kg (without batteries)
L20 B	510	27,5	-/ 24/ semi aut.	40	40	1600	1165 995 541	62
L20 E	510	27,5	230/ 50/ semi aut.	40	40	1600	1165 995 541	62
L22 B	550	27,5	-/ 24/ semi aut.	40	40	1760	1165 995 541	62
L22 E	550	27,5	230/ 50/ semi aut.	40	40	1760	1165 995 541	62

E - Mains-powered machine with voltage value

B - Battery powered machine with voltage value

Machine for commercial use

professional people

The machines are manufactured in compliance with the directives 2006/42/EC, 2006/95/EC, 2004/108/EC and with the standards IEC 60335-1 and IEC 60335-2-72.

The steel parts are subject to treatment which guarantees a long life and makes the parts oxidation-proof.



COMAC spa
Via Maestri del Lavoro, 13
37059 Santa Maria di Zevio - Verona - Italy
Tel. +39 045 8774222 - Fax +39 045 8750303
on line: www.comac.it - e-mail: com@comac.it

An ISO 9001:2008 Organisation certified by Q.C.B. Italy

