

Floor Coat Silk - 5 l

GENERAL



Tough and durable satin gloss polymer protective coating.

- Prevents wear and facilitates floor maintenance
- Gives a brilliant high gloss finish
- Can also be used as a primer (pore filler)



pH 8.5

USAGE

On a clean, dust-free and dry floor, apply 1-2 coats undiluted with a synthetic mop. Allow the floor to dry thoroughly between 2 coats (30 minutes to 1 hour under normal conditions).

Consumption: 50-100 m² / liter (per coat), depending on the porosity of the floor.

Only use this product for its specified purposes. If in doubt, first test the product in an inconspicuous area. BOMA is not responsible for any damages if the product is used incorrectly. Consult the Safety Data Sheet (SDS) for additional information.



READY TO USE

Floor Coat Silk - 5 l

TECHNICAL SPECIFICATIONS

Dimensions product (LxHxW) 18 x 30 x 13 cm

LOGISTIC DATA

Product

Article	205855
Unit	Can
Dimensions	18 x 30 x 13 cm
Gross weight	5300 g
Net weight	5150 g
EAN code	5420015519307

Packing

Quantity per packing	2
Dimensions	28 x 31 x 20 cm
Gross weight	10700 g

Pallet

Quantity per pallet	128
---------------------	-----